

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. CONTACT RESISTANCE: 30mΩ MAX.
 - 1-2. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE.
 - 1-3. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE :0.5-2.0Kgf(REF.)
 - 2-2. WITHDRAWAL FORCE :0.8-2.0Kgf(REF.)
3. LIFE TEST: 10,000 CYCLES.

6	SHELL	STAINLESS STEEL	Ni Plated	1PCS
5	SHIELDING PLATE	STAINLESS STEEL	---	1PCS
4	MD	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
3	CONTACT	COPPER ALLOY	Au/Ni Plated	1SET
2	CONTACT	COPPER ALLOY	Au/Ni Plated	1SET
1	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

料号编码:

XXX - XX XX XX X X XXXX
 公司名称 产品类别 产品上板形态 产品识别流水码
 A-USBA F-母座
 B-USBB M-公头
 C-USBC
 M-MICRO
 N-MINI
 S-贴片
 D-插件
 C-沉板
 J-夹板
 H-焊线
 XF-防水产品
 X=上板类型
 PIN 数
 06:6PIN
 16:16PIN
 24:24PIN
 以此产品为准
 包装方式
 1. TRAY (吸塑盒)
 2. TAPE (编带)
 3. TAPE (袋装)

防水胶圈

分模线毛边	ISO 3302 M2	m. m.
	SIZE	Fixed Loss
	0-4	± 0.10 ± 0.08
	4-6, 3	0.15 0.10
	6, 3-10	0.20 0.10
	10-16	0.20 0.10
	16-25	0.25 0.10
	25-40	0.35 0.10
	40-63	0.40 0.10
	63-100	0.50 0.10
	100-160	0.70 0.10
	>160	0.5% 0.10
	ANGULAR	+ 5°

本图纸适用所有橡胶材质

建议的胶圈尺寸

USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
SIGNAL NAME	GND			Vbus	CC1	Dp1	Dn1	SBU1	Vbus			GND
PIN NUMBER	B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
SIGNAL NAME	GND			Vbus	SBU2	Dn2	Dp2	CC2	Vbus			GND


ZDX 深圳市兆达鑫科技有限公司
Shenzhen zhaodaxin Technology Co., Ltd

TITLE:

TYPE C 16P 直插防水母座 H=7.18mm

工程图

THIRD ANGLE PROJECTION



UNIT:

mm

PART NO.: ZDX-CFLD162CY06

TEL:0755-29888153

WEB: <http://www.szzdjmkj.com/>

SCALE:

1:1

SIZE:

A4

SHEET:

 $1/2$