

- 1.材质:
 - 1.1胶芯: LCP+30%G.F UL94V-0
 - 1.2端子: 磷铜, T=0.12mm; 镍底, 镀金 $\times\mu$ "
 - 1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100 μ "
或亮锡100 μ "
 - 1.4接地片: 不锈钢, T=0.10mm;
 - 1.5卡片: 不锈钢, T=0.15mm;
- 2.主要特性:
 - 2.1额定电流: 0.5A
 - 2.2接触阻抗: 30m Ω MAX
 - 2.3绝缘阻抗: 100M Ω MIN 250V DC
 - 2.4耐压测试: 250V AC
 - 2.5沾锡性: 温度 $250\pm5^{\circ}\text{C}$, 时间 $5\pm0.5\text{s}$
 - 2.6整体插入力: 3.57kgf MAX
整体拔出力:1.02kgf MIN
 - 2.7使用寿命: 10000次
 - 2.8工作温度: $-30^{\circ}\text{C}\sim+80^{\circ}\text{C}$

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
IN	SIGNAL NAME	PIN	SIGNAL NAME

RECOMMENDED PCB LAYOUT(TOP VIEW)

ZDX

ZDX 深圳市兆达鑫科技有限公司
Shenzhen zhaodaxin Technology Co., Ltd

TITLE:

PART NO.: ZDX-CFMS2420048

TYPEC24P母座前插后贴L=11.95

TEL:0755-29888153

工程图

WEB: <http://www.szzdjmkj.com/>

THIRD ANGLE PROJECTION

UNIT:

SCALE:

SIZE:

SHEET:

mm

1:1

A4

1/2