

RoHS Compliant

Halogen Free

customer drawing

SPECIFICATIONS:

Contact current Rating:

1.8 Amperes for pin1&pin4.

0.25 Amperes other contacts

Dielectric Withstanding Voltage:AC 100V(RMS)

Insulation resistance:100Megohms Minimum.

Contact Resistance:

30m Ω Max for pin1&pin450m Ω Max for other contacts

Mechanical Characteristics:

Mating Force:35 Newtons.Maximum

Unmating Force:10 Newtons.Minimum.

8N Min After Durability

MATERIAL:

Housing: PBT

Contact: copper alloy(T=0.2mm)

Shell: SUS304

PLATING:

Contact: Au Plated on contact area

Tin Plated on solder area

Nickel underplating over all

Shell: Nickel Plated

operating Temperature:-55°to+85°

料号编码:

XXX - XX XX XX X X XXXX

公司名称

产品类

A-USB A-母座
B-USB B-母座
C-USB C-公头
M-MICRO
N-MINI

产品上板形态

L-立式
M-卧式S-贴片
D-插件
C-沉板
J-夹板
H-焊线

PIN 数

06:6PIN
16:16PIN
24:24PIN

以此产品为准

XF-防水系列产品

X=上板类型

包装方式

1. TRAY (吸塑盒)
2. TAPE (编带)
3. TAPE (袋装)

产品识别流水码



深圳市兆达鑫科技有限公司

Shenzhen zhaodaxin Technology Co., Ltd

TITLE:

USB-3.0侧插无边鱼叉脚

工程图

THIRD ANGLE PROJECTION



UNIT:

mm

PART NO.: ZDX-BFMD04US229

TEL: 0755-29888153

WEB: <http://www.szzdjmkj.com/>

SCALE:

1:1

SIZE:

A4

SHEET:

1/2

Pin Number	Signal Name	Pin Number	Signal Name
1	VBUS	5	SSRX-
2	D-	6	SSRX+
3	D+	7	GND
4	GND	8	SSTX-
Shell	Shield	9	SSTX+